

Vendor Sleeve Roll Specification

Revision: 1 Effective Date: 12/19/2016

Particular Specification

Parameter	Α	В	С	D	E	F	G	Н
Splices per roll	= 1</td <td><!--= 1</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td>N/A</td></td></td></td></td></td></td>	= 1</td <td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td>N/A</td></td></td></td></td></td>	=2</td <td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td>N/A</td></td></td></td></td>	=2</td <td><!--=2</td--><td><!--=2</td--><td><!--=2</td--><td>N/A</td></td></td></td>	=2</td <td><!--=2</td--><td><!--=2</td--><td>N/A</td></td></td>	=2</td <td><!--=2</td--><td>N/A</td></td>	=2</td <td>N/A</td>	N/A
Max Roll Width	100mm	150mm	90mm	90mm	105mm	90mm	11"	N/A
Max Roll Diameter	19"	19"	17"	17"	17"	17"	20"	N/A
Lay Flat	16mm -	16mm-	25mm-	25mm-	25mm-	25mm-	11"	N/A
	100mm	150mm	90mm	90mm	105mm	90mm		
Cut Length	16mm -	16mm-	25mm-	1/2"-7"	1/2"-7"	1/2"-7"	2%"-10"	N/A
	200mm	200mm	75mm					
Seam Orientation	N/A	N/A	In	In	In	In	N/A	N/A

General Specification for all sleeves except Hand Applied

- Splice tape color should be red
- Splice type should be butt
- Core Interior Diameter target is 5"
- Core Thickness should be >/=3/8"
- Max roll weight is 30 lbs

General Specification for Hand Applied sleeves

• Hand Applied sleeves should be cut and stacked

Equipment Application

Equipment ID	Primary Location	Production Line	Specification	
Accutek 42 SL1 100	1344 Industrial	12 up	Α	
Accutek 42 SL1 150	1730 Executive	Puffs 1 / Puffs 2	В	
Marburg M-5	1344 Industrial	N/A	С	
Marburg M-500-FB	1344 Industrial	6 up	D	
Marburg M-625-GT-FB	1730 Executive	Dry Rotary / 6 Cell	Е	
Marburg M-625-SVPCBF	1344 Industrial	8 up	F	
PDC R250-TS-AS	1344 Industrial	Wet Rotary	G	
Hand Applied	Any	N/A	Н	

Packaging

- All material must be packaged in a manner to prevent damage. Preferred manner is in a 6 sided box. If not boxed, then product should be secured to a pallet and overwrapped.
- All palletized non-boxed material must have a slip sheet or equivalent placed between the film and pallet.
- Non-Boxed rolls may not be stacked.
- Pallet 40x48 4 way pallet



Vendor Sleeve Roll Specification

Revision: 1 Effective Date: 12/19/2016


Material

See product drawing

Package labeling

- Core tags must be on all product to contain at the minimum the following:
 - Part number
 - o Description
 - Lot Number
 - Mfg Date
- Exterior identification must contain at the minimum the following:
 - Part number
 - Description
 - o Lot Number
 - o Mfg Date
 - o Purchase order

Wind Direction



Sleeve Reference ID

Sleeves arriving at Create-A-Pack from vendors should conform to the above specifications, and will be identified with the following reference code: [governing document] – [equipment application letter] – [wind direction]. For example, "Vendor Sleeve Roll – A - 2" refers to sleeves following the standards of this document, with specification "A", and a wind direction of 2.

Revision History

Revision	Date	Change Summary	
1	12/19/2016	Initial Release	